

Energy Smart prescriptive incentive rates

Rates effective January 1, 2024 (may change at program's discretion).



Measure	Requirements	Small Commercial Solutions	Large Commercial & Industrial	Unit
Interior lighting				
LED downlight lamp/kit	ENERGY STAR® certified.	\$13	\$8	per fixture
LED exit sign	<5 watts; must meet state fire marshal codes and be UL rated.	\$22	\$18	per lamp
T8/T12 upgrade to LED linear-4 ft.	DLC listed. For retrofitting and replacing existing fixtures: Quantity (# of units) is based on number of existing lamps being replaced.	\$9.50	\$8	per lamp
T8/T12 High Output (HO) upgrade to LED linear-4 ft.		\$10	\$10	per lamp
T5 upgrade to LED linear-4 ft.		\$7.50	\$6	per lamp
T5 High Output (HO) upgrade to LED linear-4 ft.		\$13	\$11	per lamp
T8/T12 upgrade to LED linear-8 ft.		\$17	\$14	per lamp
T8/T12 High Output (HO) upgrade to LED linear-8 ft.		\$20	\$20	per lamp
T8/T12 upgrade to LED linear-2 ft.		\$4	\$3.50	per lamp
T5 upgrade to LED linear-2 ft.		\$3.50	\$2.50	per lamp
T5 High Output (HO) upgrade to LED linear-2 ft.		\$6.50	\$5.50	per lamp
T8/T12 upgrade to LED linear-U-tube		\$10	\$8.50	per lamp
LED replacing <175W HID (lamp wattage)		DLC listed.	\$52	\$44
LED replacing 175W to 250W HID (lamp wattage)	\$52		\$44	per fixture
LED replacing 251W to 400W HID (lamp wattage)	\$130		\$110	per fixture
LED replacing 401W to 1000W HID (lamp wattage)	\$325		\$275	per fixture
LED replacing >1000W HID (lamp wattage)	\$385		\$325	per fixture
LED refrigerated case lighting (without controls)	DLC listed. Retrofits must completely remove the existing fluorescent fixture end connectors and ballasts to qualify; wiring may be reused.	\$44	\$44	per door
LED refrigerated case lighting (with controls)		\$57	\$57	per door
Exterior lighting				
LED downlight lamp/kit	ENERGY STAR® certified.	\$13	\$8	per fixture
T8/T12 upgrade to LED linear-4 ft.	DLC listed. For retrofitting and replacing existing fixtures: Quantity (# of units) is based on number of existing lamps being replaced.	\$8	\$6.50	per lamp
T8/T12 High Output (HO) upgrade to LED linear-4 ft.		\$16	\$14	per lamp
T5 upgrade to LED linear-4 ft.		\$7.50	\$6	per lamp
T5 High Output (HO) upgrade to LED linear-4 ft.		\$13	\$11	per lamp
T8/T12 upgrade to LED linear-8 ft.		\$17	\$14	per lamp
T8/T12 High Output (HO) upgrade to LED linear-8 ft.		\$31	\$27	per lamp
T8/T12 upgrade to LED linear-2 ft.		\$4	\$3.50	per lamp
T5 upgrade to LED linear-2 ft.		\$3.50	\$3	per lamp
T5 High Output (HO) upgrade to LED linear-2 ft.		\$6.50	\$5.50	per lamp
T8/T12 upgrade to LED linear-U-tube		\$11	\$9	per lamp



LED replacing <175W HID (lamp wattage)	DLC listed.	\$52	\$44	per fixture
LED replacing 175W to 250W HID (lamp wattage)		\$78	\$66	per fixture
LED replacing 251W to 400W HID (lamp wattage)		\$145	\$120	per fixture
LED replacing 401W to 1000W HID (lamp wattage)		\$365	\$310	per fixture
LED replacing >1000W HID (lamp wattage)		\$415	\$350	per fixture
LED replacing <175W Park/Athletic Field HID (lamp wattage)		\$6.50	\$6.50	per fixture
LED replacing 175W to 250W Park/Athletic Field HID (lamp wattage)		\$9	\$9	per fixture
LED replacing 251W to 400W Park/Athletic Field HID (lamp wattage)		\$15	\$15	per fixture
LED replacing 401W to 1000W Park/Athletic Field HID (lamp wattage)		\$38	\$38	per fixture
LED replacing >1000W Park/Athletic Field HID (lamp wattage)		\$56	\$56	per fixture
Lighting controls				
Daylighting controller (controlling <500W)	Quantity (# of units) is based on number of installed units. Integrated sensors built in to proposed fixtures do not qualify.	\$32	\$26	per unit
Daylighting controller (controlling >500W)		\$95	\$79	per unit
Occupancy sensor (controlling <500W)		\$48	\$40	per unit
Occupancy sensor (controlling >500W)		\$145	\$120	per unit
Occupancy sensor - daylighting control (controlling <500W)		\$56	\$46	per unit
Occupancy sensor - daylighting control (controlling >500W)		\$165	\$140	per unit
Bi-level parking garage lighting controls (controlling - 50W)	At low power, lights must consume less than 70% of full load power. Quantity (# of units) is based on number of installed units. Fixture integrated sensors do qualify for this incentive.	\$21	\$18	per unit
Bi-level parking garage lighting controls (controlling 51W to 100W)		\$63	\$53	per unit
Bi-level parking garage lighting controls (controlling 101W to 150W)		\$105	\$88	per unit
Bi-level parking garage lighting controls (controlling 151W to 200W)		\$150	\$125	per unit
HVAC				
High efficiency A/C unit	<ul style="list-style-type: none"> A/C unit (<5.4 tons): min 12.3 EER, 14.5 SEER2. A/C unit (5.4 to 11.2 tons): min. 12.2 EER, 14.8 SEER. A/C unit (11.3 to 20 tons): min. 12.2 EER, 14.8 SEER. A/C unit (20.1 to 63.3 tons): min. 10.8 EER, 13.5 SEER. A/C unit (>63.3 tons): min. 10.4 EER, 13.0 SEER Must be AHRI certified. 	\$80	\$80	per ton
High efficiency heat pump unit	<ul style="list-style-type: none"> HP unit (<5.4 tons): min. 12.3 EER, 14.5 SEER2, 8.0 HSPF2. HP unit (5.4 to 11.2 tons): min. 11.3 EER, 14.5 SEER, 12.0 HSPF. HP unit (11.3 to 20 tons): min. 10.9 EER, 14.0 SEER, 12.0 HSPF. HP unit (>20.1 tons): min. 10.3 EER, 13.0 SEER, 12.0 HSPF. Must be AHRI certified. 	\$80	\$80	per ton
High efficiency packaged terminal A/C (PTAC) unit	<ul style="list-style-type: none"> Standard PTAC (<0.6 tons): min. 13 EER. Standard PTAC (0.6 to 1.25 tons): min. 12 EER. Standard PTAC (>1.25 tons tons): min. 11 EER. Non-standard PTAC (<0.6 tons): min. 11 EER. Non-standard PTAC (0.6 to 1.25 tons): min. 9 EER. Non-standard PTAC (>1.25 tons): min. 9 EER. Must be AHRI certified. -Standard refers to PTAC dimensions of (42' wide, 16' high and 13 3/4' deep); all other dimensions are non-standard. 	\$35	\$35	per ton

High efficiency packaged terminal HP (PTHP) unit	<ul style="list-style-type: none"> • Standard PTHP (<0.6 tons): 13 EER, 3.5 COP. • Standard PTHP (0.6 to 1.25 tons): 12 EER, 3.4 COP. • Standard PTHP (>1.25 tons): 11 EER, 3.3 COP. • Non-standard PTHP (<0.6 tons): 10 EER, 3.2 COP. • Non-standard PTHP (0.6 to 1.25 tons): 9 EER, 3.1 COP. • Non-standard PTHP (>1.25 tons): 8 EER, 3 COP. • Must be AHRI certified. -Standard refers to PTAC dimensions of (42' wide, 16' high and 13 3/4' deep); all other dimensions are non-standard. 	\$35	\$35	per ton
Guestroom energy management controls	<ul style="list-style-type: none"> • Must utilize occupancy sensor to control guestroom HVAC; • Must set back thermostat setting by a minimum of 5°F. 	\$45	\$45	per unit/room
Smart thermostats for small business	<ul style="list-style-type: none"> • Smart thermostat must be ENERGY STAR® qualified. • Controlled equipment must be electrically heated or cooled. 	\$150	N/A	per unit
Commercial A/C and heat pump tune-up	<ul style="list-style-type: none"> • Incentives tiered based on the specific capacity range of the individual equipment in scope. • Trade allies submitting this measure are REQUIRED to perform test in and test-out measurements of equipment efficiencies, EER/SEER (A/C and heat pump units) and HSPF (for heat pump units only). • Inspect and clean condenser, evaporator coils, and blower. • Inspect refrigerant level and adjust to manufacturer specifications. • Measure the static pressure across the cooling coil to verify adequate system airflow and adjust to manufacturer specifications. • Inspect, clean, or change air filters. • Calibrate thermostat on/off setpoints based on building occupancy. • Tighten all electrical connections, and measure voltage and current on motors. • Lubricate all moving parts, including motor and fan bearings. • Inspect and clean the condensate drain. • Inspect controls of the system to ensure proper and safe operation. Check the starting cycle of the equipment to assure the system starts, operates, and shuts off properly. • Provide documentation showing completion of the above checklist to the utility or the utility's representative. 	\$225-\$2,500	\$225-\$2,500	per unit
Commercial chiller tune-up	<ul style="list-style-type: none"> • Incentives tiered based on the type of chiller equipment (air-cooled vs. water-cooled) • Tune-up requirements: <ul style="list-style-type: none"> • Clean condenser coil/tubes; • Check cooling tower for scale or buildup (only for water-cooled chillers); • Check contactors condition; • Check evaporator condition; • Check low-pressure controls; • Check high-pressure controls; • Check filter, replace as needed; • Check belt, replace as needed; • Check crankcase heater operation; and • Check economizer operation. • Measurement requirements: <ul style="list-style-type: none"> • Record system pressure psig; • Record compressor amp draw; • Record liquid line temperature in °F; • Record subcooling and superheat temperatures in °F; • Record suction pressure psig and temperature in °F; • Record condenser fan amp draw; and • Record supply motor amp draw. 	\$9-\$15	\$9-\$15	per ton

Commercial duct sealing	<ul style="list-style-type: none"> Eligible only for system with central air conditioning with less than 50% of ducts in the conditioned space. Total leakage is the only accepted method of duct testing. Minimum 25% leakage rate reduction required. Incentives capped at 35% leakage rate reduction. Ducts sealed with long-lasting materials such as UL 181A or UL 181 B-approved foil tape. Fabric-based duct tape is not allowed. 	\$70	\$70	per CFM leakage reduction
High efficiency air-cooled chiller	<ul style="list-style-type: none"> Air-cooled chiller (<150 tons): min 9.7 full-load EER, 15.8 IPLV EER. Air-cooled chiller (>150 tons): min 9.7 full-load EER, 16.1 IPLV EER. 	\$50	\$50	per ton
High efficiency positive displacement water-cooled chiller	<ul style="list-style-type: none"> Water-cooled PD chiller (<75 tons): min full-load kW/ton 0.78, IPLV kW/ton 0.5. Water-cooled PD chiller (75 to 150 tons): min full-load kW/ton 0.75, IPLV kW/ton 0.49. Water-cooled PD chiller (150 to 300 tons): min full-load kW/ton 0.68, IPLV kW/ton 0.44. Water-cooled PD chiller (>300 tons): min full-load kW/ton 0.63, IPLV kW/ton 0.41. 	\$17	\$17	per ton
High efficiency centrifugal water-cooled chiller	<ul style="list-style-type: none"> Water-cooled cent. chiller (<300 tons): min full-load kW/ton 0.695, IPLV kW/ton 0.44. Water-cooled cent. chiller (300 to 600 tons): min full-load kW/ton 0.595, IPLV kW/ton 0.39. Water-cooled cent. chiller (>600 tons): min full-load kW/ton 0.585, IPLV kW/ton 0.38. 	\$30	\$30	per ton
Refrigeration				
ECM motor for freezer or cooler	Applicable only to refrigerated cooler and freezer fans.	\$100	\$100	per unit
Evaporator fan controller for freezer or cooler	Controller must turn on fan only when the system's thermostat is calling for the compressor to operate.	\$65	\$65	per motor controlled
Anti-sweat heater controls for freezer or cooler	<ul style="list-style-type: none"> Controller must sense dew point temperature of case exterior environment and vary power supplied to heaters accordingly. Applicable for retrofit only; not applicable for new equipment with integrated controls. 	\$35	\$35	per linear ft. of case
Refrigerated case night covers	Applicable for retrofit only, not applicable for new cases with integrated night covers.	\$20	\$20	per linear ft. of case
ENERGY STAR® solid door refrigerator	Must be ENERGY STAR® certified.	\$95	\$95	per unit
ENERGY STAR® solid door freezer	Must be ENERGY STAR® certified.	\$165	\$165	per unit
Strip curtains for walk-in coolers	Applicable to coolers with damaged strip curtains or without pre-existing strip curtains.	\$4	\$4	per sq. ft. covered
Strip curtains for walk-in freezers	Applicable to freezers with damaged strip curtains or without pre-existing strip curtains.	\$8	\$8	per sq. ft. covered
Strip curtains for refrigerated warehouse doors	Applicable to doors with damaged strip curtains or without pre-existing strip curtains.	\$8	\$8	per sq. ft. covered
Door gaskets - coolers (refrigeration)	Baseline standard is walk-in or reach-in cooler or freezer with worn-out, defective gaskets. Efficiency standard for this measure is a new, better-fitting gasket.	\$2	\$2	per linear ft.
Door gaskets - freezers (refrigeration)		\$14	\$14	per linear ft.
Auto door-closers - coolers (refrigeration)	Auto, hydraulic-type door closer on main walk-in cooler or freezer insulated opaque door(s). Must firmly close the door when it is within 1 inch of full closure.	\$113	\$113	per unit
Auto door-closers - freezers (refrigeration)		\$157	\$157	per unit



Commercial kitchen				
ENERGY STAR® commercial electric fryer		\$250	\$250	per unit
ENERGY STAR® commercial electric steam cooker		\$1,865	\$1,865	per unit
ENERGY STAR® electric convection oven	Electrically heated and ENERGY STAR® certified.	\$230	\$230	per unit
ENERGY STAR® electric griddle		\$45	\$45	per linear ft. of width
Food service kitchen exhaust controls	Controls must automatically adjust flow of exhaust ventilation system using variable speed fan motor.	\$600	\$600	per exhaust fan HP
ENERGY STAR® commercial dishwasher	Must be electrically heated and ENERGY STAR® certified.	\$600	\$600	per unit
Pre-rinse spray valves	Maximum flow rate for new equipment of 1.07 GPM. Applicable only to equipment supplied with electrically heated water.	\$35	\$35	per unit
Miscellaneous				
Computer power management	Software must put the computer equipment into a reduced power state (sleep mode) when the computer is inactive.	\$22	\$22	per unit
Window film	<ul style="list-style-type: none"> • Applicable to clear single or double-pane glazing with a solar heat gain factor (SHGC) >0.66. • Applicable to east-, west-, and south-facing windows only. The SHGC of the proposed film must be less than 0.50. • Not applicable to low E windows, windows with existing solar films or solar screens. • Film must meet the following standards: ASTM E408, ASTM E308, ASTM E903, ASTM G90, ASTM G26, ASTM E84. • Incentives tiered based on orientation and HVAC system type. 	\$.30-\$1.50	\$.30-1.50	per sq. ft. of window area
Efficient windows	<ul style="list-style-type: none"> • Installation of efficient and/or premium windows which provide a lower U-value and SHGC vs. existing windows or prevailing codes and standards. • Applicable to clear single- or double-pane glazing with a solar heat gain factor (SHGC) greater than 0.70. • Must be independently tested and certified according to the standards of the National Fenestration Rating Council (NFRC). • Must meet or exceed the following performance ratings: Efficient Windows - SHGC <= 0.25 and U factor <= 0.40; Premium Windows - SHGC <= 0.23 and U factor <= 0.36. 	\$0.50	\$0.50	per sq. ft. of window area
Advanced power strips	Multi-plug power strip that automatically disconnects loads depending on the power draw of a specified "master" load.	\$8	\$8	per unit
Low-flow faucet aerators	<ul style="list-style-type: none"> • Maximum flow rate for new equipment of 1.5 GPM. • Applicable only to faucets supplied with electrically heated water. 	\$6	\$6	per aerator
Low-flow showerheads	<ul style="list-style-type: none"> • Maximum flow rate for new equipment of 2.0 GPM. • Applicable only to showers supplied with electrically heated water. 	\$7	\$7	per unit

